

DATASHEET ICX POWER ASCENDER



GENERAL

Art.Nr:	POA-030-0	Net weight:	9.90 kg
GTIN:	4030281310426	Gross weight:	9.90 kg
Customs tariff number:	84253100		



DATASHEET

ICX POWER ASCENDER

The ultralight, compact entry-level ActSafe ICX power ascender has been developed for a safe and efficient transport of persons in hard-to-reach areas. Paired with a rope, the ActSafe ICX forms an incredibly flexible system for the straightforward and cost-efficient cleaning and maintenance of complex intuitive structures. Its operation effortlessly managed with a thumb wheel, enabling precise work. Thanks to its IP55 rating, the ActSafe ICX can be used in all weather conditions. Rope loading is straightforward, streamlining your workflow and saving valuable Additionally, the control of the ActSafe ICX can be taken over by a second person on the ground using a remote control. This allows for the automatic ascent or descent of the individual operating the device, in case they are unable to do so themselves. Operating and utilizing the ActSafe ICX is quickly and easily learned through user training.

Ultralight, compact personal power ascender

Fast and secure rope loading

Easy control with an intuitively operated thumb wheel or remote control

- · WLL 185kg or max. 1 person
- Battery and Charger not included

FEATURES

Battery range at 20° C & 100 kg load:	230 m	
Application areas:	Various	
Energy source:	Removeable Battery	
Colour:	Various	
Underwater operations:	No	
Water dust resistance:	IP 55	
Charging time:	80 minutes	
Maximum descent speed:	24 m/min	
Max. ascent rate:	24 m/min	
Maximum compatible rope diameter:	11.00 mm	
Maximum temperature:	40 °C	
Minimum descent speed:	1 m/min	
Min. ascent rate:	1 m/min	
Minimum compatible rope diameter:	11.00 mm	
Minimum temperature:	-10 °C	
Emergency descent function:	Yes	
Emergency stop function:	Yes	
Remote control range:	50 m	
DIMENSIONS		

MATERIAL

Working load limit:

185.00 kg



DATASHEET ICX POWER ASCENDER

Material:

Steel, Aluminium, Nylon